

MY FLOOR LAMINATE

MyFloor Laminate - the non-slip laminate with impressive performance and utmost versatility! Our embossed and non-slip laminate, awarded with a B1 certificate, guarantees not only safety but also outstanding performance.

With durability that withstands even intensive cleaning with cleaning and sweeping machines, MyFloor Laminate sets new standards for resilient flooring. Whether used as floor film or in other creative applications, experience the performance and quality that elevate your space to a new level.

Durability

Up to 12 months for indoor applications.

Printing method

UV curable inks, solvent, ecosolvent and latex.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

It is recommended to handle the used material and production waste as industrial waste.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.



Uses

- POS
- Events
- Reception area
- Shopping center

Features & Benefit

- Easy application and removal
- Removal without adhesive residue
- Excellent durability
- Great heat resistance and dimensional stability
- Good chemical resistance
- Cleaning with machines guaranteed



Technical Information

MyFloor Laminate

Size	Width: 1.372 m Length: 30.48 m	
Material	Embossed, anti-slip laminate	240μ +/- 5μ
Adhesive	Permanent solvent adhesive	20g/m2 +/-3g/m2
Certificate	Slip resistance	R10
	Fire Classification	DIN EN 13501-1