

## SIDE WALK

SideWalk is designed to be used for short to midterm applications dependent on where the product is applied. The product can be used on asphalt, cement and untreated stone, pavement and many more surfaces but the surface should not be very uneven and structured. The material can easily be removed from such surfaces. The special adhesive is designed to work outdoor on rough surfaces.

### Durability

The durability of SideWalk is dependent the mechanical use of the surface where it is applied. We recommend a maximum use of 6 months. Life time can be significantly extended with EasyProtect liquid varnish.

### Printing method

UV curable inks and latex.

### Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

### Waste handling

SideWalk is designed to be fully recyclable.



### Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.



### Uses

- Shop entries, pedestrian areas & stairways
- Bus, tramway or metro stations, airports
- Sport events: Bicycle race, marathons etc.
- Museums, meetings and other cultural events

### Features & Benefit

- Easy to apply and remove
- PVC free



## Technical Information

## SideWalk

Size	Width: 1.372 m      Length: 30.48 m	
Material	Polyurethane with sand grain	347 $\mu$ +/- 10 $\mu$
Adhesive	Permanent acrylic solvent	66 $\mu$ +/- 5 $\mu$
Certificates	Slip-resistance	R11
	Flame resistance / Flammability	B1 / M1
Application	Minimum application temperature	+10°C / +50°F

## Chemical Resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	I	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion  
 I = recommended for intermittent exposure only  
 NR = not recommended