

SPORT WALK

SportWalk can be used for short to midterm applications. The foil consists of a dimension stable film with a textured resilient surface. The product provides a resilient, durable, slip resistant surface for a large variety of applications. The foil is characterized by an extremely secure and slip resistant surface, a chemical resistance and longevity. The waterproof adhesive and the therewith associated durability of the foil guarantee a versatile usability.

Durability

The durability depends on the way the product has been applied as well as on the condition of the surface and the amount and type of traffic on the area. SportWalk has to be applied on a completely dry surface. Our experiences suggest the following:

- Indoor up to 2 months
- Outdoor 4 to 6 weeks

Life time can be significantly extended with EasyProtect liquid vanish.

Printing method

UV curable inks, solvent, ecosolvent and latex

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

It is recommended to handle the used material as industrial waste.



Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.

Uses

- Sports events
- Road shows

Features & Benefit

- Extremely secure with its slip-resistant
- Can be cut to shape
- Robust against abrasion
- Good chemical resistance - laboratory report from Quality Labs
- Print and apply - No lamination required



Technical Information

SportWalk

Size	Width: 1.30 m Length: 30.48 m	
Material	Calandered vinyl	450 μ +/- 10 μ
Adhesive	Permanent acrylic solvent	50 μ +/- 5 μ
Certificates	Slip-resistance	R10
	Antibacterial certificate	ISO 22196 (Mod)
Application	Minimum application temperature	+10°C / +50°F

Peel Adhesion to	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	55oz/in (66N/100 mm)	20oz/in (22N/100mm)	40oz/in (44N/100mm)
24 hours dwell	75oz/in (82N/100 mm)	25oz/in (27N/100 mm)	55oz/in (60N/100 mm)

Chemical Resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	R	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion
 I = recommended for intermittent exposure only
 NR = not recommended

* Colour and lot variances of coated surfaces including paints, powder coatings, lacquers, stains and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface. **At temperatures below +10 °C the surface has to be pre-treated with a gas burner.

CONTINENTAL GRAFIX AG

Lettenstrasse 2
 6343 Rotkreuz
 Switzerland

CONTACT

Phone: +41 41 763 66 88
 Fax: +41 41 763 60 14
 Email: info@continentalgrafix.com

MORE INFORMATION

For a detailed overview of our products please visit:
www.continentalgrafix.com