

ULTRA PROTECTION LAMINATE

UltraProtection Laminate is designed for medium to long-term applications depending on where the product is applied. UltraProtection Laminate is very resistant against wear and other influences provided that they result from common use of the product. At the same time the product is very flexible in processing and bonding. For extended use, we recommend edge sealing to achieve the desired long durability.

PanoRama X-treme or Asphalt Walk Smooth with UltraProtection Laminate are the perfect product combinations if you need a long-lasting floor sticker for up to 3 years.

Durability

The durability of Ultra Protection Laminate is depending on the application, especially on the surface where it has been applied as well as the mechanical strain. Based on our experience we recommend a maximum use of 2 to 3 years.

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

It is recommended to handle the used material and production waste as industrial waste.



Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specification.



Uses

- Long term murals
- Treads / Walkways
- Shelf markings
- Entrance area
- High traffic graphics

Features & Benefit

- Simple application and processing despite the thickness
- Very robust
- Extremely slip-resistant
- Withstands extreme impacts

Technical Information**UltraProtection Laminate**

Size	Width: 1.37 m Length: 15.00 m	
Material	clear, slip-resistant textured vinyl	600μ +/- 10μ
Adhesive	Clear, permanent solvent adhesive	50 g/m2 +/- 5 g/m2
Certificates	Slip-resistance	R9
Application	Minimum application temperature	+10°C / +50°F

CONTINENTAL GRAFIX AG
Lettenstrasse 2
6343 Rotkreuz
Switzerland

CONTACT
Phone: +41 41 763 66 88
Fax: +41 41 763 60 14
Email: info@continentalgrafix.com

MORE INFORMATION
For a detailed overview of our
products please visit:
www.continentalgrafix.com