

PANORAMA BLACK

panoRama Black provides effective daytime privacy, enhanced visual protection, and effective solar shading. Its innovative black-on-black technology with a clear adhesive helps limit visibility into interior spaces while maintaining outward visibility and allowing natural daylight to enter. Manufactured from high-quality calendered vinyl and equipped with a clear, semi-permanent adhesive, panoRama Black combines high-quality workmanship, premium material quality, and reliable performance.

Durability

Up to 1 year in Central European climate conditions. Removable without adhesive residue within 6 months. Adhesion increases over time. Do not apply to the following surfaces: fresh paint or ink, polycarbonate, or certain types of PVC (no complete list is available). If in doubt, test on a small area before final application whenever possible.

Storage

1 year when stored at +15°C to +20°C (+59°F to +68°F) and at a relative humidity between 45% and 65%.

Advice

Do not allow the film to come into contact with cleaning agents containing solvents or ammonia. Clean windows using soap and water only. Rinse thoroughly and allow the glass to dry completely. ALWAYS apply the film to clean and dry glass surfaces only. Please refer to our application instructions.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made as to the accuracy or suitability of this product for specific applications.



Uses

- Shop windows
- Building façades
- All applications up to 12 months

Features & Benefits

- Maximum contrast and excellent see-through visibility
- Excellent removability, even after extended use
- Clear, semi-permanent adhesive allows for easy removal
- Ideally combined with panoRama Cast or panoRama Protect laminate

Technical information

panoRama Black

Size	Width: 1.372 m Length: 25.00 m, 50.00 m	
Material	Self-adhesive, perforated calendered vinyl film. Printable black front side and black reserve side	150µ +/- 10µ
Adhesive	Removable, semi-permanent clear acrylic adhesive	
Open area Printable area	20% open area 80% printable area	
Liner	Single Liner	120 µ +/- 10µ
	Humidity resistance	good
	Solvent resistance	good
Application	Minimum application temperature	+10°C to +30°C (+50°F to +86°F)
	Minimum service range temperature	- 17°C to +50 °C (+0°F to +122°F)