

panoRama Lightbox

panoRama Lightbox is a perforated, cast film engineered to support day-to-night light management for long term illuminated channel letters, light boxes, signs and displays. When applied to the exterior surface, the channel letter or signage will appear black during the day (when not lit) and take on the color of the translucent sign face at night.

Available in an 80/20 film/open ratio for maximum contrast and light diffusion.

Durability

Up to 7 years on light boxes in Central European conditions. Adhesion increases with time, it will be difficult to remove. Not to be used on: fresh paint or ink, polycarbonate, certain PVCs (not a complete list). For critical substrates, please test before use.

Shelf life

1 year, stored at +15 to +20° C (+59 to +68° F) and relative humidity between 45% and 65%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warrantees of any kind are made to the accuracy of suitability for specific applications.



Advice

Avoid contact with solvents or cleaners containing ammonia. Clean windows with soap and water. Rinse and dry the glass after cleaning. ALWAYS clean and dry glass before use. Please refer to our application instructions, which are designed for accuracy of suitability for specific applications

Uses

- Light boxes
- Channel letters
- Signs and displays
- Backlit external signage viewed from a distance

Features & Benefit

- Great dimensional stability
- Maximum contrast and light diffusion

Technical information participation		panoRama Lightbox
Size	Width: 1.372 m Length: 25 m 1.372 m 50 m	
Material	Self-adhesive, perforated, calendared cast vinyl film.	140μ +/- 10μ
Adheisve	Permanent clear adhesive	
Open area	20% open area	
Liner	Special liner finish	150g +/- 10μ
Application	Minimum application temperature	+10°C / +50°F
	Minimum service range temperature	- 17°C / +0°F