

PANORAMA SOLAR

panoRama Solar – Endless possibilities for solar modules

panoRama Solar transforms solar modules into versatile design elements. Printed façade designs allow modules to blend seamlessly into their surroundings and open up completely new applications. This makes it possible to use solar modules in places that were previously unthinkable – generating energy in a smarter and more aesthetic way. Suitable both for new installations and for already installed projects, to be used only on vertical solar modules.

The white front film is compatible with UV-curable inks. Thanks to a special high-performance adhesive, it adheres permanently and reliably to the module surface – yet can be easily replaced or removed if necessary.

Durability

Up to 5 years warranty when used in a Central European climate.

Printing method

UV curable inks

Lamination

Cold lamination should only be carried out using the specially designated laminate. The lamination rollers must be clean and undamaged, and the edges must be protected with edge protection tape.

Shelf life

1 year, stored at +15 to +25° C (+59° F to +77° F) and relative humidity between 20% and 70%. For use at +5 °C to +40 °C (+41 °F to +104 °F) and at a relative humidity between 30% and 70%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific.



Uses

- Vertical walls

Features & Benefit

- Unique and individual design possibilities
- Creative freedom
- Visual highlights
- No standard solutions

Technical information

Size	Width: 1.372 m Length: 25m /50m	
Material	Perforated, light-transmitting high-performance cast vinyl film	100 μ +/- 10 μ
Adhesive	Special adhesive compound	
Liner	Double siliconized paper liner	135g +/- 10 μ
	Moisture resistance	Very good
	Solvent resistance	Very good
Application	Application and removal temperature	+20°C up to +35°C
	Operating temperature	- 10°C to +60 °C

Technical information

panoRama Solar

Size	Width: 1.372 Length: 25m /50m	
Material	Cast PVC Film / capable- of receptive sunlight	50 μ +/- 10 μ
Adhesive	Special adhesive compound	
Liner	PET frosted	135g +/- 10 μ
Application	Application and removal temperature	+20°C up to +35°C
	Operating temperature	- 10°C to +60 °C

CONTINENTAL GRAFIX AG

Lettenstrasse 2
6343 Rotkreuz
Switzerland

CONTACT

Phone: +41 41 763 66 88
Fax: +41 41 763 60 14
Email: info@continentalgrafix.com

MORE INFORMATION

For a detailed overview of our products please visit:
www.continentalgrafix.com