

ITac Green

ITac Green is a multi-layer cast polypropylene film that can be easily recycled.

It is extremely dimensionally stable and thanks to the adhesive technology it is easy to apply and remove. The product can be used several times and if the adhesive side is dirty it can be washed off with lukewarm water.

As laminate for ITac Green we recommend to use our eco-friendly panoRama

Green Laminate with anti-graffiti coating or panoRama Protect or panoRama Cast. These are ideal for lamination and offers the appropriate UV protection.

Durability

When printed up to 3 years under mid European conditions. Adhesion may increase depending on the surface and length of time. Not to be applied on: fresh paint or ink, polycarbonate, certain PVC (no exhaustive list available). If you are not sure, please, test prior to application.

Printing method

UV curable inks, latex, (digital) offset and screen printing.

Shelf life

1 year, stored at +15 to +25° C (+59° F to +77° F) and relative humidity between 45% and 70%.

Advice

If you would like to reuse the product you have to apply it back to the original liner and pack it in a plastic store to pretend the adhesive from drying out. ITac Green und Take care when removing the film from the surface, as the cast and flexible material can get optical traces very easily. ITac Green pro must be handled with the greatest care because it can quickly be damaged. We recommend to laminate the product to give it more protection. Prevent from contact with solvent or ammoniac based cleaner. Clean window with soap and water. Rinse and dry glass after cleaning. ITac Green und ITac Green Pro are not designed for structured surfaces. Don't use it on materials like copper, PVC, polished aluminum. If you apply it on vehicles make sure the surface is undamaged and in perfect condition.



Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Uses

- All kinds of smooth surfaces (glas, car body, polished stone, films etc.)

Features & Benefit

- Up to 3 years durability warranty for applications under mid European conditions.
- Easy application and removal
- Removal without residue
- Great heat resistance and dimensional stability



Tecnical Information

ITac Green

Size	Width: 1.372 m Length: 25.00 m, 50.00 m	
Material	Cast Polypropylene with silver back	75µ +/- 10µ
Adhesive	Synthetic natural rubber adhesive	
Liner	PET	125µ +/- 10µ
Application	Application temperature	+15°C to +45°C (+59°F to +113°F)
	Removal recommended at +10°C or more. In critical cases, please test prior to removal on corresponding surfaces to avoid residues.	+10°C to +30°C (+50°F to +86°F)

CONTINENTAL GRAFIX AG
 Lettenstrasse 2
 6343 Rotkreuz
 Switzerland

CONTACT
 Phone: +41 41 763 66 88
 Fax: +41 41 763 60 14
 Email: info@continentalgrafix.com

MORE INFORMATION
 For a detailed overview of our products please visit:
www.continentalgrafix.com