

PANORAMA GREEN LAMINATE

Discover the innovation of panoRama Green Laminate - a clear and glossy polyester laminate, specifically designed for laminating print media, particularly for panoRama Green. When combined with panoRama Green, this laminate provides additional protection for the perforated film. As an added bonus, panoRama Green Laminate boasts anti-graffiti properties, making it ideal for this application as well. Perfect for long-term outdoor use, this product offers optimal color resistance to UV light thanks to the additional UV protection in the laminate film. panoRama Green Laminate provides additional UV protection and supports long-lasting colour performance in outdoor applications.

Durability

Up to 5 years in mid European conditions.

Shelf life

1 year, stored at +15°C to +25°C (+59°F to +77°F) and relative humidity between 45% and 70%.

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.



Advice

Please check our applying and removal advices for panoRama. Handle the products with great care.

Uses

- All One-way-vision films applied on flat surfaces
- Especially developed to cover perforated film so that no dust, humidity or other contamination can penetrate the perforation
- Recommended for applications where the best UV resistance and clarity is required even at extreme conditions
- Anti-graffiti protection

Features & Benefit

- Very high UV-resistance
- Resistant against cleanser, alcohol, solvents and diluted acids and alkalis
- Laminate stripes can be used as edge guard



Technical Information		panoRama Green
Size	Width: 1.372 m Length: 25.00 m, 50.00 m	
Material	Polyester film	20µ +/- 10% 28g/m2 +/-10%
Adhesive	Clear permanent acrylic (solvent based) adhesive	
Laminating method	Cold	
Liner	One side siliconized polyesterfilm	30µ +/- 10µ / 42g/m2 +/-10%
Certificate	Flammability	B1
	TÜV Approval Germany	~ D5750 with panoRama Green Laminate
Application	Shrinkage	0 %
	Cohesion/ ultimate adhesion	Very high
	Chemical resistance	No effects
	Adhesion	High
	Minimum application and removal temperature	+10°C (+50°F)
	Minimum service range temperature	- 20°C to +140 °C (-4°F to +284°F)

CONTINENTAL GRAFIX AG

Lettenstrasse 2
6343 Rotkreuz
Switzerland

CONTACT

Phone: +41 41 763 66 88
Fax: +41 41 763 60 14
Email: info@continentalgrafix.com

MORE INFORMATION

For a detailed overview of our
products please visit:
www.continentalgrafix.com