

Application My Floor Film

My Floor Film is a classic, calendered white foil with grey backing, which is used for interior bonding with the matching My Floor Laminate R10 on various floor coverings. The sandwich also has B1 certification. The expected durability can be up to 6 months, depending on the usage. Other areas of application are textured walls, doors and glass surfaces, where the film can be removed very easily.

If you now follow the processing instructions below, you and your customers will have a lot of satisfaction with the product.

Print

Please make sure that the printing film has taken over the ambient temperature before printing, there are often temperature differences between the warehouse and production rooms that must first be compensated by the product. For very good printing results, set the print setting to «Vinyl Film Glossy» or «Cast».

Printing process

Solvent, eco-solvent, UV-curable inks, offset and screen printing.
Latex printing at a temperature of 90 - 95 °C

Drying time

After printing, store the **My Floor Film** print foil in a way that best allows the print to dry and any solvents to evaporate. If stored flat and open, the print must dry for at least 24 hours, otherwise 48 hours. After that, the product is ready for the lamination process. Latex prints have a general processing guideline for drying for foils given by the manufacturer HP.

Laminating

When inserting the print film and laminate, make absolutely sure that there are no pulls and that the tension is identical for both materials. This prevents the material from "tunnelling" or "rolling up" and makes application much easier. Smaller prints can also be laminated without a laminator. However, this variant is very challenging for the user and is therefore only recommended for experienced persons. When subsequently "trimming" the print, we recommend that you avoid sharp corners and round them off.

Attach

My Floor Film has been specially developed for a wide variety of substrates in the floor sector. The special adhesive adapts very well to the conditions. Here, the surface temperature should be at least **10°C** during application. It is important to press the edges and borders properly and neatly so that the film nestles against the substrate. The surface to which the film is to be applied must be well cleaned and, above all, free of grease and dust. We recommend applying the film dry.

Disassembly

The specially developed adhesive of My Floor Film can be removed from almost all surfaces without leaving any residue and without causing any problems. It is important to pay attention to the removal temperature of +10°C to + 30°C. Pull the film off evenly at a flat angle. This is the quickest way to remove it. If possible, two people should carry out the removal process together.

If you now follow all these instructions, nothing will stand in the way of your successful campaign. If you have any specific questions, please contact your Continental Grafix representative or write to info@continentalgrafix.com. Have fun!